

OpenReport

The *OpenReport* action opens a report in normal view or in report design view.

tags:
[Actions](#)

Applies to ...

Object	Description
DoCmd	Root class. When present, its name must be " DoCmd " but the object name is optional.

Syntax

[[DoCmd](#).]OpenReport(*ReportName*, *View*)

Argument	Optional	Type or Symbol	Description
ReportName	No	String	The name of the report to open. This argument is NOT case-sensitive.
View	Yes	acViewDesign acViewNormal acViewPreview	The view in which the query will open. <i>acViewNormal</i> and <i>acViewPreview</i> are equivalent. Default is <i>acViewNormal</i> .

The symbolic constants can be included in your code by copying and pasting next lines:

```
Const acViewDesign = 1
Const acViewNormal = 0
Const acViewPreview = 2
```

Remarks

- If the report was built with the Sun Report Builder extension, this extension is required to get the report open.
- If the *view* argument is *acDesign*, the query will get opened in Design mode. However any further action is not supported by the Access2Base API.
- The *OpenReport* action must not be triggered from a **standalone form**.

Error messages

Report '...' could not be opened
Report '...' not found
Action not applicable in this context

See also

[Close](#)
[OpenForm](#)
[OpenQuery](#)
[OpenSQL](#)
[OpenTable](#)

Example

```
Const acViewNormal = 0
OpenQuery("myQuery", acViewNormal)
```

Bookmark this page » » [OpenReport](#)